



Jiaxing Selected Technology Co., Ltd.

PRODUCT: PTFE SERIES OUTER

Item	Unit	H300	H301	H302	H303	M601	M602	M603
Base fabric	Fiberglass							
Coating	PTFE							
Color	Turns white after sun exposure							
Flame retardant	B1							
Thickness	(mm)	1.0±0.1	0.8±0.08	0.6±0.06	0.75±0.075	0.7±0.07	0.5±0.05	0.6±0.06
Total weight	g/m2	1800±180	1450±145	1150±115	1300±130	1350±135	950±95	1200±120
Tensile strength	(Warp) N/5cm	9500	8000	6000	7000	7000	5000	6000
Tensile strength	(Weft) N/5cm	8500	8000	5500	7000	6000	5000	5500
Tear strength	(Warp) N/5cm	500	400	350	400	350	350	350
Tear strength	(Weft) N/5cm	500	400	350	400	350	350	350
Light	%	10	12	15	15	15	15	15
App	Arch-Membranes Outer							

These indicated technical data are based on average results. actual data 's tolerance +-5%.Due to production procedures slight deviations can occur.All technical data are in accordance with the present standard of knowledge and give product information without legal binding.All data apply to new products

Company : Jiaxing Selected Technology Co., Ltd.

Ad : No.1, Fenghuang dongyuan,Dingqiao,Haining,Zhejiang.China. 314413

Email: admin@selectedfabric.com

Website: www.selectedfabric.com